

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/049240 A1

(51) International Patent Classification⁷: **B08B 9/043**,
9/045, C23C 16/44

(21) International Application Number:
PCT/GB2004/004768

(22) International Filing Date:
12 November 2004 (12.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0326707.7 17 November 2003 (17.11.2003) GB

(71) Applicant (for all designated States except US): **THE
BOC GROUP PLC** [GB/GB]; Chertsey Road, Windle-
sham, Surrey GU20 6HJ (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CLEMENTS,
Christopher, James, Philip** [GB/GB]; Boc Edwards,

Kenn Business Park, Kenn Road, Clevedon, North Som-
erset BS21 6TH (GB). **WHITAKER, Ian, Richard**
[GB/GB]; Boc Edwards, Kenn Business Park, Kenn Road,
Clevedon, North Somerset BS21 6TH (GB).


(74) Agent: **BOOTH, Andrew, Steven**; The Boc Group Plc,
Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: EXHAUST GAS TREATMENT



(57) Abstract: An attachment (10) for an inlet pipe (14) to a wet scrubber or other device comprises a sleeve (16) having an open end (18) adapted to be detachably connected to a flanged end (12) of the inlet pipe (14). A shaft (30) is moveable within the sleeve (16), and a scraper (34) is attached to one end of the shaft (30). The shaft (30) forms part of a pneumatic cylinder (40) attached to the other end of the sleeve (16). In use, the shaft (30) is reciprocally moved to cause the scraper (34) to dislodge particulates deposited within the pipe (14). Heated gas such as nitrogen or dry air is injected into the sleeve (16) to prevent scrubbing liquid from condensing within the sleeve (16) and thus inhibit particulate deposition therein.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.